

July 22, 2025

RE: AMICO Architectural Metals compatibility with DELTA®-FASSADE membranes

To Whom it May Concern:

Dörken Systems Inc has reviewed the technical data for AMICO Architectural Metals for use with Dörken Systems Inc. mechanically attached DELTA®-FASSADE S and self-adhered DELTA®-FASSADE SA with AMICO Architectural Metals.

DELTA®-FASSADE is intended for use on open joint facades with up to 50% exposure of the overall façade, with a maximum of 2-inch-wide joints. DELTA®-FASSADE products are suitable for use with all AMICO Architectural products with a visual and mechanical opening of 50% or less can also be used on custom designed panels provided these limits are not exceeded. This includes standard profiles of expanded mesh, perforated panels and laser cut metal as well as any bespoke patterns AMICO can produce.

Any panel profiles where visual openings do not exceed 50% with mechanical openings exceeding of 50% of the overall area are to be reviewed by Dörken Systems Inc. on a project specific basis.

DELTA®-FASSADE membranes are specifically designed for use in demanding open-joint cladding systems, where much of the insulation and substructure is exposed to the elements.

The matte black color of DELTA®-FASSADE membranes add depth and dimension while improving the visual appeal of any project. Its UV-stable, water-resistive barrier allows you to maximize building protection without compromising aesthetics. DELTA®-FASSADE membranes maintain their appearance and quality, so you're protected without taking away from the aesthetics of your build.

Kind regards,

Michael Hooper

Michael Hooper MBSc.

Building Science Manager

mhooper@dorken.com

C +1 (905)658-0576

T +1 (905)563-3255

www.dorken.com

A DÖRKENGROUP Company